

Technical Data Sheet
Polypropylene – Impact Copolymer
Produced in the United States

TotalEnergies Petrochemicals & Refining USA, Inc. Polymers Americas

## **Description**

**Polypropylene 5571** is a high impact copolymer with a melt flow of 7 g/10min

5571 is characterized by significantly improved impact resistance and good processability.

5571 has been developed specifically for cast film applications.

## **Characteristics**

	Method	Unit	Typical Value
Rheological Properties			
Melt Flow	ASTM D-1238	g/10 min	7
Mechanical Properties			
Tensile, Strength at Yield	ASTM D-638	psi (MPa)	3,400 (23)
Elongation at Yield	ASTM D-638	%	7
Flexural Modulus	ASTM D-790	psi (MPa)	170,000 (1,170)
Izod Impact (Notched)			
@ 23°C	ASTM D-256	ftlbs/in. (J/m)	3.5 (187)
@-20°C	ASTM D-256	ftlbs/in. (J/m)	1.4 (75)
Thermal Properties <sup>(1)</sup>			
Melting Range	Total Method	°F (°C)	320-329 (160-165)
Heat Deflection	ASTM D-648	°F (°C)	194 (90)
Vicat Softening Point	D-1525	°F (°C)	298 (148)
Other Physical Properties			
Density	D-1505	g/cm <sup>3</sup>	0.905

<sup>(1)</sup> Data developed under laboratory conditions and are not to be used as specification, maxima or minima.

Rev: Sept 2021

TOTALENERGIES PETROCHEMICALS & REFINING USA, INC. POLYMERS AMERICAS 1201 Louisiana Street Suite 1800 Houston, TX 77002 www.polymers.totalenergies.com

TECHNICAL CENTER P.O. Box 1200 Deer Park, Texas 77536 Phone: 281-884-7500

1-800-344-3462